

PRO



prover 7000



- Accommodates from:
 - 1 up to 6 single -
- 750 x 500 mm racks or
 - 1 to 4 single -
- 800 x 600 mm racks
- Perfect humidity and temperature for consistent product using Revent's filtered air wash system.
- Modular design. May be shipped assembled or knocked down.
- Interior and exterior in stainless steel material, jointing profiles of aluminium.
- Hydraulic door closers.
- All controls at eye level.
- Interior and exterior bumper guards are standard.
- No flushing required.
- 50 mm thick sealed polystyrene insulation.
- Available also in larger prover and retarder/prover rooms.



Design

- Interior and exterior in stainless steel material, jointing profiles of aluminium
- Meets bakery industry sanitation standards
- Modular design, may be shipped assembled or knocked down
- Insulated with plastic foam panels throughout
- Stainless steel floor is standard
- Electric heaters

Controls

- Digital controls for time, temperature and humidity

Climate conditioner

- Unique humidification and temperature conditioning unit is virtually maintenance free
- Air filter and standard air wash system prevent build-up of minerals and provide perfect humidity conditions
- Temperature is controlled by an electronic thermostat

Utility Requirements

- Water Supply
 - G 1/2" 2 kg/cm² (200 kN)
- Drain
 - 3/4" connection back
- Electrical
 - 3 phase

NOTE: All voltages available, check with factory

TYPE	SIZE AND NUMBER OF RACKS FOR VARIOUS TRAY SIZES				HEATING CAPACITY kW	OUTSIDE DIMENSIONS			NUMBER OF DOORS AND WIDTH OF DOOR
	Single 457x660	Single 750x500	Single 800x600	Single 1000x800		Width	Depth	Height	
7011	1	1			4	880	1150	2300	1 x 820
7012	2	2	1	1	4	1150	1530	2300	1 x 1087
7021	2	2			4	1500	1150	2300	2 x 714
7022	4	4	2	2	6	2005	1600	2300	2 x 968
7023	6	6	4	2	6	2005	2202	2300	2 x 968

Continuous product development is a Revent policy. Therefore, we reserve the right to change specifications and/or design without prior notice.

P7000uk041125



Prover 7000 remote control

Revent sales representative



REVENT INTERNATIONAL AB
 PO BOX 714, SE-194 27 Upplands Väsby, Sweden
 Tel: +46 8 590 006 00 Fax: +46 8 590 942 10
 E-mail: info@revent.se www.revent.com